



Wireless Paging Amps



MA-1200

- UHF receiver
- 1,200 Watt amplifier
- Cooling fan
- 110/220 Volt switchable
- Circuit protection indicator
- A/B speaker selection switches
- Unbalanced RCA inputs
- Channel A & B speaker outputs
- Dimensions: 19"W x 3.5 "H x 19"D
- Weight: 46 lbs.
- Rack mountable

MA-2400

- UHF receiver
- 2,400 Watt amplifier
- Cooling fan
- 110/220 Volt switchable
- Circuit protection indicator
- A/B speaker selection switches
- Unbalanced RCA inputs
- Channel A & B speaker outputs
- Dimensions: 19"W x 3.5 "H x 19"D
- Weight: 53 lbs.
- Rack mountable

Specifications

Model	MA-1200	MA-2400
Bridge Mono Power	1000W	1600W
1KHz 0.1% THD	1500W	2400W
Signal to Noise	103dB	105dB
Slew Rate	60V/uS	60V/uS
Damping Factor	400:1	450:1
Frequency Response	+/-0.1dB, 20Hz+20kHz	+/-0.1dB, 20Hz+20kHz
THD	≤0.01% Rated Power @ 8 ohms 1kHz	≤0.01% Rated Power @ 8 ohms 1kHz
IMD	≤0.01% Rated Power @ 8 ohms	≤0.01% Rated Power @ 8 ohms
Input Sensitivity	0.775V, 1.0V, 1.55V	0.775V, 1.0V, 1.55V
Input impedance	10K/20K ohms, unbalanced or balanced	10K/20K ohms, unbalanced or balanced
Input CMRR	≤-75dB	≤-75dB
Cross talk	≤-70dB	≤-70dB
LEP indicator	Signal, Protect, Dctive, Clip/Limiting	Signal, Protect, Dctive, Clip/Limiting
Main power supply	110V/60HZ	110V/60HZ
Supply power	1050W	1650W
Weight	46 lbs.	53 lbs.
Dimensions	19"W x 3.5"H x 19"D	19"W x 3.5"H x 19"D

